

智能功率模块：600V /7A 三相全桥驱动 NSMD07S60C1

1 特点

- 内置 6 个 600V/7A 的 MOS (Typ. $R_{ds,on} = 0.6\Omega$ @25°C)
- 内置高压栅极驱动电路 (HVIC)
- 内置欠压保护
- 内置自举二极管
- 内置温度检测功能
- 内置栅驱动电路的电压范围从 12V 到 20V
- 3 个独立的负电流端用于需要电流检测的应用
- 兼容 3.3V 和 5V 的 MCU 接口，高电平有效
- 优化并采用了低电磁干扰设计
- 绝缘等级 1500Vrms/min

2 典型应用

- 室内/户外空调
- 冰箱压缩机
- 排风扇
- 风扇
- 空气净化器
- 洗碗机水泵

3 芯片概述

3.1 特点


NSMD07S60C1 是高度集成、高可靠性的三相无刷直流电机驱动电路，主要应用于风扇类的小功率电机驱动。该模块内置了 6 个功率 MOS 管和 3 个半桥高压栅极驱动电路。

NSMD07S60C1 内部集成了欠压保护功能，提供了优异的保护和失效保护操作。由于每一相都有一个独立的负直流端，其电流可以分别单独检测。

NSMD07S60C1 采用了高绝缘、易导热和低电磁干扰的


设计，提供了非常紧凑的封装体，使用非常方便，尤其适合内置于电机的应用和要求紧凑安装の場合。

3.2 芯片信息



Part Number	Package	Body size
NSMD07S60C1	SOP23	29mm x 12mm

Functional Block Diagram



4 Ordering Guide

Part Number	LOGO	Package	Package	SPQ
NSMD07S60C1	 NSMD07S60C1 XXXXX	SOP23	Tape & Reel	500

5 Revision history

Version	Content	Time
V1.0	Create	2023.11.10



INDEX

1 FEATURES AND BENEFITS	1
2 TYPICAL APPLICATIONS	1
3 DESCRIPTION	1
3.1 CHARACTERISTIC	1
3.2 CHIP INFORMATION	1
4 ORDERING GUIDE	2
5 REVISION HISTORY	2
6 FUNCTION PIN DESCRIPTION	4
7 PRODUCT SPECIFICATIONS	5
7.1 ABSOLUTE MAXIMUM RATINGS	5
7.2 RECOMMENDED OPERATING CONDITIONS	5
7.3 ELECTRICAL CHARACTERISTICS	6
8 NSMD07S60C1 DESCRIPTION	8
9 PACKAGE INFORMATION	9
10 DISCLAIMER	10

6 Function Pin Description




Figure6-1 23-Pin Top view

Table6-1 Lead Definitions

Number	Symbol	Description
1	COM	IC Common Supply Ground
2	$V_{B(U)}$	Bias Voltage for U-Phase High-Side MOSFET Driving
3	$V_{CC(U)}$	Bias Voltage for U-Phase IC and Low-Side MOSFET Driving
4	$IN_{(UH)}$	Signal Input for U-Phase High-Side
5	$IN_{(UL)}$	Signal Input for U-Phase Low-Side
6	N.C	No Connection
7	$V_{B(V)}$	Bias Voltage for V-Phase High Side MOSFET Driving
8	$V_{CC(V)}$	Bias Voltage for V-Phase IC and Low Side MOSFET Driving
9	$IN_{(VH)}$	Signal Input for V-Phase High-Side
10	$IN_{(VL)}$	Signal Input for V-Phase Low-Side
11	V_{TS}	Output for HVIC Temperature Sensing
12	$V_{B(W)}$	Bias Voltage for W-Phase High-Side MOSFET Driving
13	$V_{CC(W)}$	Bias Voltage for W-Phase IC and Low-Side MOSFET Driving
14	$IN_{(WH)}$	Signal Input for W-Phase High-Side
15	$IN_{(WL)}$	Signal Input for W-Phase Low-Side
16	N.C	No Connection
17	P	Positive DC-Link Input
18	$U, V_{S(U)}$	Output for U-Phase & Bias Voltage Ground for High-Side MOSFET Driving
19	N_U	Negative DC-Link Input for U-Phase
20	N_V	Negative DC-Link Input for V-Phase
21	$V, V_{S(V)}$	Output for V-Phase & Bias Voltage Ground for High-Side MOSFET Driving
22	N_W	Negative DC-Link Input for W-Phase
23	$W, V_{S(W)}$	Output for W Phase & Bias Voltage Ground for High-Side MOSFET Driving

7 Product specifications

7.1 Absolute Maximum Ratings

Exceeding the limit maximum rating may cause permanent damage to the device. All voltage parameters are rated with reference to COM and an ambient temperature of 25°C.

Inverter Part (each MOSFET unless otherwise specified)

Symbol	Definition	Conditions	Rating	Units
V_{DSS}	Drain-Source Voltage of Each MOSFET		650	V
V_{GSS}	Gate-Source Voltage of Each MOSFET	$T_C = 25^\circ\text{C}$	± 30	V
I_D	Each MOSFET Drain Current, Continuous	$T_C = 25^\circ\text{C}$	TBD	A
I_{DP}	Each MOSFET Pulse Current, Peak	$T_C = 25^\circ\text{C}$, Less than 100us	TBD	A
T_J	Maximum Junction Temperature		150	$^\circ\text{C}$

Control Part (each HVIC unless otherwise specified)

Symbol	Definition	Conditions	Rating	Units
V_{CC}	Control Supply Voltage	Applied between V_{CC} and COM	20	V
V_{BS}	High-side Bias Voltage	Applied between V_B and V_S	20	V
V_{IN}	Input Signal Voltage	Applied between V_{IN} and COM	$-0.3 \sim V_{CC} + 0.3$	V

Bootstrap Diode Part (each bootstrap diode unless otherwise specified)

Symbol	Definition	Conditions	Rating	Units
V_{RRMB}	Maximum Repetitive Reverse Voltage		600	V
I_{FB}	Forward Current	$T_C = 25^\circ\text{C}$	0.25	A
I_{FPB}	Forward Peak Current, Peak	$T_C = 25^\circ\text{C}$, Under 1ms Pulse Width	0.5	A

Total System

Symbol	Definition	Conditions	Rating	Units
T_J	Operating Junction Temperature		$-40 \sim 150$	$^\circ\text{C}$
T_{STG}	Storage Temperature		$-40 \sim 150$	$^\circ\text{C}$
V_{ISO}	Isolation Voltage	60Hz, Sinusoidal, 1 minute, Connect Pins to Heat-Sink Plate	1500	Vrms

Thermal Resistance

Symbol	Definition	Conditions	Rating	Units
$R_{\theta JC}$	Junction to Case Thermal resistance	Each MOSFET under Inverter Operating Condition	7.1	$^\circ\text{C}/\text{W}$

Note1: To insure safe operation of the IPM, the average junction temperature should be limited to $T_J \leq 150^\circ\text{C}$ ($@T_C \leq 100^\circ\text{C}$).

7.2 Recommended Operating Conditions

Symbol	Parameter	Condition	MIN.	TYP.	MAX.	Units
V_{PN}	Supply Voltage	Applied between P and N	-	300	400	V
V_{CC}	Control Supply Voltage	Applied between V_{CC} and COM	12		18.5	V
V_{BS}	High-Side Bias Voltage	Applied between V_B and V_S	12		18.5	V
$V_{IN(ON)}$	Input ON Threshold Voltage	Applied between V_{IN} and COM	3.0	-	VCC	V
$V_{IN(OFF)}$	Input OFF Threshold Voltage		0	-	0.6	V
t_{dead}	Blanking Time for Preventing Arm-Short	$V_{CC} = V_{BS} = 13.5 \sim 16.5 \text{ V}$, $T_J < 150^\circ\text{C}$	1.0	-	-	us
f_{PWM}	PWM Switching Frequency	$T_J < 150^\circ\text{C}$	-	15	-	KHz

7.3 Electrical Characteristics

Valid for temperature range at $T_A = 25^\circ\text{C}$, unless otherwise specified

Inverter Part(each MOSFET unless otherwise specified)

Symbol	Parameter	Condition	MIN.	TYP.	MAX.	Units
BV_{DSS}	Drain - Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 100\text{ }\mu\text{A}$	650	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0\text{ V}, V_{DS} = 650\text{ V}$	-	0.1	20	μA
$R_{DS(on)}$	Static Drain-Source Turn-On Resistance	$V_{DS} = 10\text{ V}, I_D = 4\text{ A}$	-	481	700	$\text{m}\Omega$
V_{FSD}	Drain - Source Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 2.5\text{ A}$	-	3.8	-	V
t_{ON}	Switching Times	$V_{PN} = 300\text{ V}, V_{CC} = V_{BS} = 15\text{ V}, I_D = 0.5\text{ A}$ $I_N = 0\text{ V} \leftrightarrow 5\text{ V}$, Inductive Load $L = 3\text{ mH}$ High- and Low-Side MOSFET Switching	-	840	-	ns
t_{OFF}			-	430	-	ns
t_{rr}			-	75	-	ns
E_{ON}			-	43	-	μJ
E_{OFF}			-	14	-	μJ
RBSOA	Reverse Bias Safe Operating Area	$V_{PN} = 400\text{ V}, V_{CC} = V_{BS} = 15\text{ V}, I_D = I_{DP}$, $V_{DS} = B_{VDS}, T_J = 150^\circ\text{C}$ High- and Low-Side MOSFET Switching	Full Square			

Control Part(each HVIC unless otherwise specified)

Symbol	Parameter	Condition		MIN.	TYP.	MAX.	Units
I_{QCC}	Quiescent VCC Supply Current	$V_{CC} = 15\text{ V}$ $V_{IN} = 0\text{ V}$	Applied between VCC and COM	-	80	180	μA
I_{QBS}	Quiescent VB Supply Current	$V_{BS} = 15\text{ V}$ $V_{IN} = 0\text{ V}$	Applied between $V_{B(U)} - U$, $V_{B(V)} - V$, $V_{B(W)} - W$	-	30	60	μA
V_{CCD}	Low-side UVLO threshold	VCC Under-Voltage Protection Detection Level		-	11.5	-	V
V_{CCR}		VCC Under-Voltage Protection Reset Level		-	10.5	-	V
V_{BSD}	High-side UVLO threshold	VBS Under-Voltage Protection Detection Level		-	11.5	-	V
V_{BSR}		VBS Under-Voltage Protection Reset Level		-	10.5	-	V
V_{TS}	HVIC Temperature Sensing Voltage Output	$V_{CC} = 15\text{ V}, T_{HVIC} = 25^\circ\text{C}$		320	650	900	mV
V_{IH}	ON Threshold Voltage	Logic HIGH Level	Applied between V_{IN} and COM	-	-	2.6	V
V_{IL}	OFF Threshold Voltage	Logic LOW Level		0.8	-	-	V

Control Part(each bootstrap diode unless otherwise specified)

Symbol	Parameter	Condition	MIN.	TYP.	MAX.	Units
VF	BSD Forward voltage	$I_F = 0.1\text{ A}, T_C = 25^\circ\text{C}$	-	2.8	-	V
t_{rrB}	Reverse Recovery Time	$I_F = 0.1\text{ A}, T_C = 25^\circ\text{C}$	-	80	-	ns
R	BSD Current Limiting Resistor		-	100	-	ohm




Figure7-1 Temperature Profile of V_{TS} (Typical)

8 NSMD07S60C1 Description

Typical application circuit




Figure8-1 Example of RC-coupling parameter 390 ohm and 1nF

Recommended Application Circuit and MCU Interface with parameter


Notes:

1. RC-coupling ($R_1 - R_6$ and $C_0 - C_6$) at each input of IPM product and MCU are useful to prevent improper input signal caused by controller scheme and /or surge-noise.
2. All the filter capacitors should be connected close to IPM product, and they should have good characteristics for rejecting high-frequency ripple current.



9 Package Information

SOP23 Package Outlines



10 免责声明

- 本公司（国硅集成电路技术（无锡）有限公司）所提供的 NSMD07S60C1 产品及其相关数据表（以下简称“产品”）并未针对极高可靠性要求的应用进行设计或测试，如生命支持系统、飞机控制系统或其他一旦失效可能导致严重人身伤害和/或物质损失的应用。在使用本产品于此类应用之前，请务必咨询您附近的本公司代表。
- 本公司不对因超出产品规格（包括但不限于最大额定值、操作条件范围或其他参数）的瞬时或持续使用而导致的设备故障承担责任。用户应确保在使用本产品时遵守所有规定的规格和条件。
- 本数据表所述的产品性能、特性和功能均基于产品独立状态下的测试结果，并不构成产品在用户产品或设备中安装后的性能、特性和功能的保证。对于无法在产品独立状态下评估的症状和状态，用户应始终在其产品或设备中安装并测试产品以进行验证。
- 尽管本公司致力于提供高质量、高可靠性的产品，但所有半导体产品均存在一定的失效概率。这种概率性失效可能导致事故或事件，从而危及人身安全、引发火灾或烟雾，或造成其他财产损失。因此，在设计设备时，用户应采取安全措施，以防止此类事故或事件的发生。这些措施包括但不限于安全设计保护电路和防错电路、冗余设计以及结构设计。
- 如本数据表所述的任何产品或技术数据受当地出口管制法律法规的管辖，则在获得相关当局根据上述法律颁发的出口许可证之前，不得出口此类产品。
- 本数据表及其所包含的信息（包括电路图和电路参数）仅供示例之用，并不保证用于批量生产。本公司认为本数据表中的信息是准确可靠的，但对于其使用或任何侵犯第三方知识产权或其他权利的情况，本公司不作出任何明示或暗示的保证。
- 由于产品/技术改进等原因，本数据表及其中所述的信息可能会在不事先通知的情况下发生变更。在设计设备时，请参考您打算使用的国硅驱动产品的“交货规范”。
- 本声明基于 2023 年 11 月的信息编制，并可能在不通知的情况下进行更改。